

TOOLCHAIN

GnuCOBOL `cobc -x p.cob exe -m module(.so) -j build+run - --free free format --std=ibm IBM dialect - Wall -g --debug run-time checks -I dir copybooks -cobcrun MOD runs a module - env COB_LIBRARY_PATH, COB_FILE_PATH, COB_SET_TRACE, COB_TRACE_FILE, COB_RUNTIME_CONFIG`

z/OS procs IGYWCL (compile+link) · IGYWCLG (+go).
Options: ARCH(n) OPT(0|1|2) TEST SSRANGE
NUMCHECK TRUNC(STD|OPT|BIN) SQL CICS LIST MAP
XREF OFFSET · cob2 on z/OS UNIX

FIXED-FORMAT RULER

1-6 seq	7 8-11 A	12-72 Area B	73-80
---------	----------	--------------	-------

Col 7: * comment · - continuation / page eject · D debug line. Area A: divisions, sections, paragraphs, 01/77. Area B: statements. Free format: >* comment; switch with >>SOURCE FORMAT FREE. Statements end with a scope terminator (END-IF); period ends a sentence.

PROGRAM SKELETON

```
IDENTIFICATION DIVISION.
PROGRAM-ID. PAYROLL.
ENVIRONMENT DIVISION.
CONFIGURATION SECTION.
INPUT-OUTPUT SECTION.
FILE-CONTROL. SELECT ...
DATA DIVISION.
FILE SECTION.          FD, 01
WORKING-STORAGE SECTION. per run unit
LOCAL-STORAGE SECTION. per call
LINKAGE SECTION.        parameters
PROCEDURE DIVISION [USING ...].
MAIN-PARA.
    PERFORM ...
    STOP RUN.          >* or GOBACK
```

STOP RUN ends the run unit; GOBACK returns to caller.
Nested programs: PROGRAM-ID. X ... END PROGRAM X.
inside another; COMMON, INITIAL.

DATA DIVISION

Levels 01 record · 02-49 subordinate · 66 RENAMES · 77 stand-alone · 88 condition name. FILLER unnamed.

```
01 REC.
05 ID      PIC 9(5) VALUE ZERO.
05 NAME    PIC X(20).
05 ST      PIC X VALUE 'A'.
08 88 ACTIVE VALUE 'A'.
01 RAW REDEFINES REC PIC X(26).
66 K RENAMES ID THRU NAME.
01 AMT IS TYPEDEF PIC S9(7)V99 COMP-3.
INITIALIZE grp (numeric--0, alnum--spaces) · VALUE
sets initial value · SPACE(S) ZERO(S) HIGH-VALUE LOW-
VALUE QUOTE ALL "x"
```

PICTURE SYMBOLS

9 digit	X any char	A letter
N national	U UTF-8	S sign (no byte)
V implied point	P scaling	(n) repeat

Edited: Z zero—space · * check fill · \$ currency (float) · , insert · + = sign · CR DB credit/debit · B blank · 0 zero · / slash

PIC	Value	Shown
ZZ, Z99,99	1234.5	_1,234.50
\$\$\$,\$\$9.99	45.6	___\$45.60
***,**9.99	12.3	***12.30
--Z9	-7	__-7
ZZ9.99CR	-5	__5.00CR
99/99/9999	12312026	12/31/2026

USAGE

Usage	Bytes	Notes
DISPLAY	1/digit	zoned; default; sign in zone
COMP-3	[(n+1)/2]	sign nibble C + D – F u packed
COMP/BINARY	2 / 4 / 8	1-4 / 5-9 / 10-18 digits; big-endian
COMP-5	2/4/8	native, full range
COMP-1/-2	4 / 8	float / double
NATIONAL	2/char	UTF-16
UTF-8	1-4/ch	2023 std
INDEX	4	table subscript
POINTER	4 / 8	SET ADDRESS OF

COMP-3 PIC S9(4) COMP-3 = 3 bytes:

0	1	2	3	4	C
pad	d1	d2	d3	d4	sign
+1234 = 01 23 4C		-1234 = 01 23 40		unsigned	
12345 = 12 34 5F					

TABLES

```
01 T.
05 E OCCURS 1 TO 100 TIMES
    DEPENDING ON N
    ASCENDING KEY IS K
    INDEXED BY IX.
    10 K PIC 9(4).
SET IX TO 1 SET IX UP BY 1
SEARCH E AT END ... WHEN K(IX)=X ... END-SEARCH
SEARCH ALL E WHEN K(IX)=X ... END-SEARCH
Subscripts start at 1. SEARCH ALL is a binary search and
needs a sorted table with ASCENDING|DESCENDING KEY.
SORT table ON ASCENDING KEY sorts in memory.
Subscripts: T(I J); reference modification:
FLD(start:len).
```

MOVE & ARITHMETIC

MOVE numeric aligns on the decimal point (truncates high/low digits); alphanumeric left-justifies and pads with spaces; CORRESPONDING matches names; MOVE X TO A B C.

```
ADD A TO B GIVING C
SUBTRACT A FROM B
MULTIPLY A BY B GIVING C
DIVIDE A INTO B GIVING Q REMAINDER R
COMPUTE X ROUNDED = (A + B) ** 2 / C
ON SIZE ERROR DISPLAY "OVERFLOW"
NOT ON SIZE ERROR ...
END-COMPUTE
ROUNDED (default nearest-away; MODE IS ...). Without ON
SIZE ERROR results truncate silently.
```

CONDITIONS, IF, EVALUATE

Relation = < > >= <= NOT · class IS
NUMERIC|ALPHABETIC · sign IS
POSITIVE|NEGATIVE|ZERO · 88-level IF ACTIVE ·
compound AND OR NOT, abbreviated A > 1 AND < 9
IF A > B ... ELSE ... END-IF
EVALUATE TRUE
WHEN X < 0 ...
WHEN 0 THRU 9 ...
WHEN OTHER ...
END-EVALUATE
EVALUATE A ALSO B WHEN 1 ALSO ANY ...

PERFORM

```
PERFORM PARA PERFORM A THRU B
PERFORM PARA 5 TIMES
PERFORM PARA UNTIL EOF
PERFORM WITH TEST AFTER UNTIL X > 9
PERFORM VARYING I FROM 1 BY 1
    UNTIL I > N
    AFTER J FROM 1 BY 1 UNTIL J > M ...
PERFORM UNTIL EXIT
... EXIT PERFORM / EXIT PERFORM CYCLE
END-PERFORM
inline
```

Default test is **before**. Avoid GO TO.

STRINGS, FUNCTIONS, DATES, I/O

STRING A DELIMITED BY SIZE
B DELIMITED BY SPACE
INTO T WITH POINTER P
ON OVERFLOW ... END-STRING
UNSTRING S DELIMITED BY ", " INTO A B C
TALLYING IN N
INSPECT S TALLYING N FOR ALL "x"
INSPECT S REPLACING ALL "a" BY "b"
INSPECT S CONVERTING to TO UP

FUNCTION LENGTH TRIM UPPER-CASE LOWER-CASE
REVERSE NUMVAL NUMVAL-C MAX MIN MOD REM ABS
SQRT INTEGER ORD CHAR RANDOM CURRENT-DATE
INTEGER-OF-DATE DATE-OF-INTEGER

Dates ACCEPT d FROM DATE YYYYMMDD · DAY · TIME ·
CURRENT-DATE = 21 chars YYYYMMDDhhmmsshh+hhmm · I/O
DISPLAY a b UPON CONSOLE · ACCEPT x · ACCEPT x
FROM ARGUMENT-VALUE · ENVIRONMENT.

ERRORS

AT END sequential read · INVALID KEY keyed I/O · ON
EXCEPTION CALL / ACCEPT / JSON / XML · ON OVERFLOW
STRING / UNSTRING · ON SIZE ERROR arithmetic. Check
FILE STATUS after every I/O.

DECLARATIVES.
H SECTION. USE AFTER STANDARD ERROR
PROCEDURE ON IN-FILE.

...
END DECLARATIVES.

EC-* exception conditions (EC-SIZE, EC-BOUND) ·
RETURN-CODE special register becomes the step condition
code (MOVE 8 TO RETURN-CODE); STOP RUN WITH ERROR
STATUS (GnuCOBOL 3.2).

FILES

```
SELECT F ASSIGN TO "x.dat" >* DD name on z/OS
ORGANIZATION IS SEQUENTIAL|LINE SEQUENTIAL|
INDEXED|RELATIVE
ACCESS MODE IS SEQUENTIAL|RANDOM|DYNAMIC
RECORD KEY IS K
ALTERNATE KEY IS A WITH DUPLICATES
FILE STATUS IS FS.
FD F. 01 F-REC ...
```

OPEN	READ	WRITE	REWRITE	DELETE	START
INPUT	yes	-	-	-	idx
OUTPUT	-	yes	-	-	-
I-O	yes	idx/rel	yes	idx/rel	idx
EXTEND	-	yes	-	-	-

```
READ F NEXT|PREVIOUS INTO w [KEY IS k] AT
END|INVALID KEY · START F KEY >= k · CLOSE F. VSAM
KSDS = INDEXED; ESDS = sequential; RRDS = RELATIVE.
```

FILE STATUS CODES

00 OK	35 file not found
02 OK, duplicate alt key	37 no permission/mode
04 OK, record length differs	39 attribute conflict
05 OK, optional file absent	41 already open
10 end of file	42 not open (close)
21 key sequence error	43 no prior READ
22 duplicate key	44 record size boundary
23 record not found	46 no valid next record
24 boundary violation	47 READ, not open INPUT/I-O
30 permanent error	9x implementor-defined (VSAM)

First digit: 0 success · 1 at end · 2 invalid key · 3 permanent · 4 logic · 9 vendor.

SORT, MERGE & PATTERNS

```
SD SW. 01 SR. 05 K PIC X(5). ...
SORT SW ON ASCENDING KEY K
USING IN GIVING OUT
SORT SW ON DESCENDING KEY K
INPUT PROCEDURE IS P1 >* RELEASE rec
OUTPUT PROCEDURE IS P2 >* RETURN SW AT END
MERGE MW ON ASCENDING KEY K
USING F1 F2 GIVING F3
```

Control break: read sorted input; when key ≠ saved key, print subtotal, reset, save key; final total at EOF. **Balance line:** two files sorted by key, compare keys: low key advances; equal = match/update.

SUBPROGRAMS

```
CALL "SUB" USING BY REFERENCE A
BY CONTENT B
BY VALUE N
RETURNING R
ON EXCEPTION ... END-CALL
CANCEL "SUB"
PROCEDURE DIVISION USING A B.
FUNCTION-ID. F. ... RETURNING R.
```

Static CALL "X" literal bound at link (z/OS NODYNAM),
dynamic loaded at run time (DYNAM option, CALL ident).
Default is by reference; BY CONTENT passes a copy; BY
VALUE is for C. LOCAL-STORAGE is fresh per call; INITIAL
program resets each call.

JSON & XML

```
JSON GENERATE J FROM REC COUNT IN N
NAME OF fld IS "x" SUPPRESS fld
ON EXCEPTION ... END-JSON
JSON PARSE J INTO REC WITH DETAIL
NAME OF fld IS "x"
XML GENERATE X FROM REC COUNT IN N
XML PARSE X PROCESSING PROCEDURE P
ON EXCEPTION ... END-XML
```

XML PARSE event handler reads XML-EVENT, XML-TEXT.
JSON-CODE / XML-CODE hold the error code.

JCL

```
//PAYJOB JOB (ACCT),'NAME',CLASS=A,
// MSGCLASS=X
//STEP1 EXEC PGM=PAYROLL,PARM='X'
//STEPLIB DD DSN=MY.LOADLIB,DISP=SHR
//INFILE DD DSN=MY.IN,DISP=SHR
//OUTFILE DD DSN=MY.OUT,DISP=(NEW,CATLG,DELETE),
// SPACE=(CYL,(5,1),RLSE)
// DCB=(RECFM=FB,LRECL=80,BLKSIZE=0)
//GDG DD DSN=MY.GDG(+1),DISP=(NEW,CATLG)
//SYSOUT DD SYSOUT=*
data
/*
// IF STEP1.RC <= 4 THEN
// ENDF
```

DISP=(status,normal,abnormal) : NEW OLD SHR MOD
/ CATLG KEEP DELETE PASS. RC 0 ok, 4 warning, 8 error,
12 severe, 16 terminal.

DB2 (EMBEDDED SQL)

```
EXEC SQL INCLUDE SQLCA END-EXEC.
EXEC SQL SELECT NAME INTO :H-NAME :IND
FROM T WHERE ID = :H-ID END-EXEC.
EXEC SQL DECLARE C1 CURSOR FOR
SELECT ... FOR UPDATE OF X END-EXEC.
EXEC SQL OPEN C1 END-EXEC.
EXEC SQL FETCH C1 INTO :A :B END-EXEC.
EXEC SQL CLOSE C1 END-EXEC.
EXEC SQL COMMIT END-EXEC.
```

SQLCODE 0 success · +100 not found / end of cursor · <0
error (–305 null w/o indicator, –803 duplicate key, –904
resource). Prepare: precompile or **coprocessor** (SQL option)
→ DBRM → BIND PACKAGE/PLAN → compile → link → run
under DSN.

CICS

```
EXEC CICS RECEIVE MAP('M1') MAPSET('S1')
INTO(MAPI) RESP(RC) END-EXEC.
EXEC CICS SEND MAP('M1') FROM(MAPO)
ERASE END-EXEC.
EXEC CICS READ FILE('F') INTO(R)
RIDFLD(K) END-EXEC.
EXEC CICS LINK PROGRAM('P')
COMMAREA(C) END-EXEC.
EXEC CICS XCTL PROGRAM('Q') END-EXEC.
EXEC CICS RETURN TRANSID('TRN1')
COMMAREA(C) END-EXEC.
```

Pseudo-conversational: task sends a map, returns with
TRANSID + COMMAREA, ends; next input starts a new task
(EIBCALEN=0 first time). Test RESP against
DFHRESP(NORMAL|NOTFND) ... LINK returns; XCTL does
not.

COMMON ABENDS (z/OS)

S0C7	data exception: invalid packed/zoned data (bad file layout; NUMCHECK, IS NUMERIC)
S0C4	protection: subscript out of range, bad CALL parameters, unset pointer (SSRANGE)
S0CB	divide by zero (ON SIZE ERROR)
S322	time limit: endless loop or volume growth
S806	load module not found (STEPLIB)
S013	OPEN failed: RECFM / LRECL mismatch
U0038	Language Environment abnormal end; read CEEDUMP

TOOLING & TESTING

VS Code: IBM Z Open Editor or Broadcom COBOL
Language Support, plus Zowe Explorer (data sets, USS,
jobs). **Zowe CLI:** zowe zos-files list data-set
"HLQ.*" · zowe zos-files download data-set · zowe
zos-files upload file-to-data-set · zowe zos-jobs
submit data-set · zowe zos-jobs list jobs.
Debug: GnuCOBOL -g --debug, COB_SET_TRACE, --
coverage (gcov); z/OS TEST option, z/OS Debugger,
CEEDUMP. **Test:** COBOL Check, zUnit, Test4z, Galasa,
GnuCOBOL & shell scripts in CI.

LEGACY → MODERN

GO TO / ALTER →	periods everywhere → scope terminators (1985)
PERFORM + EVALUATE	
NEXT SENTENCE →	EXAMINE → INSPECT
CONTINUE	
2-digit years → CURRENT-DATE / YYYYMMDD	OO COBOL → Java interop (6.4)
fixed format → free format	Micro Focus → Rocket (2002)
Zowe v1 → Zowe v3	COBOL Check → zUnit / Test4z / Galasa