

Magento Cheat Sheet

Magento Open Source / Adobe Commerce 2.4.9 (GA 2026-05-12) · Mage-OS 3.6.0 (2026-10-14)
Checked 2026-10-27 · 2.4.10 is still alpha (2.4.10-alpha1, 2026-10-13)

EDITIONS: WHAT EACH ALLOWS

Open Source	Free code base (OSL-3.0, AFL-3.0), self-hosted, in-process PHP only. No I/O Events, Upgrade Compatibility Tool, B2B or extended-support patches. repo,magento.com asks for Marketplace keys.
Mage-OS	Community distribution, repo.mage-os.org, no keys; PHP ~8.3 ~8.4 ~8.5; no eventing modules.
Commerce on-prem	Licensed, you operate it. In- and out-of-process (events, webhooks, App Builder), B2B, extended support.
Commerce on Cloud	PaaS, single-tenant, Fastly included, manual updates, enforced deadlines.
Cloud Service	SaaS, versionless, out-of-process only , no Luma, Edge Delivery storefront, Adobe IMS.

VERSIONS, SUPPORT, ENFORCEMENT

Line	GA	Std. end	Ext. end
2.4.9	2026-05-12	2029-05-31	n/p
2.4.8	2025-04-08	2028-05-31	n/p
2.4.7	2024-04-09	2027-05-31	2028-05-31
2.4.6	2023-03-14	2026-08-11	2027-08-31
2.4.5	2022-08-09	2025-08-12	2026-08-11
2.4.4	2022-04-12	2025-04-12	2026-04-14

n/p = not published; extended support is Adobe Commerce only. Latest: 2.4.8-p5, 2.4.7-p10, 2.4.6-p15; 2.4.9 has no -pN, only monthly builds (2.4.9-2026-oct).

Cloud enforcement: dependencies by **2026-10-30** or 2027-05-31; 2.4.4/2.4.5 upgrade by 2027-06-01, 2.4.6/2.4.7 by 2028-06-01. Admin or traffic is suspended.

Patches: -pN; isolated patch (needs latest -pN); hotfix (any supported version); individual patch.

REQUIREMENTS (ON-PREM, LATEST PATCH)

	2.4.9	2.4.8-p5	2.4.7-p10
PHP	8.5 (8.4 upgrade only)	8.4, 8.3	8.3, 8.2
DB	MariaDB 12.3, MySQL 8.4	MariaDB 11.4/11.8, MySQL 8.4	MariaDB 10.11/11.8
Search	OpenSearch 3	OpenSearch 3, ES 8	OS 2.19/3, ES 8
Cache	Valkey 9	Valkey 8.1	Valkey 8.1
Other	RabbitMQ 4.3 or Artemis 2, Composer 2.10, Varnish 8, nginx 1.30		

2.4.9: native MVC replaces Laminas MVC, symfony/cache replaces Zend_Cache, HugerTE replaces TinyMCE.

INSTALL

```
composer config -g http-basic.repo.magento.com
"<public-key>" "<private-key>"
composer create-project \
  --repository-url=https://repo.magento.com/ \
  magento/project-community-edition=2.4.9 \
  /var/www/shop
# Commerce: magento/project-enterprise-edition
composer create-project \
  --repository-url=https://repo.mage-os.org/ \
  mage-os/project-community-edition=3.6.0 \
  /var/www/shop
bin/magento setup:install \
  --base-url=http://localhost/ \
  --db-host=db --db-name=magento \
  --db-user=magento --db-password='<pw>' \
  --admin-user='<user>' --admin-password='<pw>' \
  --search-engine=opensearch \
  --opensearch-host=search \
  --cache-backend=valkey \
  --cache-backend-valkey-server=cache
# also --admin-email, --first-name, --lastname
```

Run composer check-platform-reqs first; memory_limit=2G, OPcache on, docroot pub/. A random Admin URI is chosen unless --backend-frontname; read it with bin/magento info:adminuri.

TESTING, UPGRADES, PERFORMANCE

- Tests:** dev/tests/unit, integration, api-functional, bin/magento dev:tests:run static, Jasmine, MFTF 3.6.0 (Test/Mftf).
- Upgrade:** back up, maintenance:enable, Composer update, setup:upgrade, setup:di:compile, indexer:reindex, maintenance:disable. Search: config:set catalog/search/engine opensearch; cache:set; config:set --cache-backend=valkey.
- Speed:** production mode, Valkey (cache, page cache, sessions), Varnish 8 or Fastly, indexers on schedule, real cron.

bin/magento: DAILY COMMANDS

Info	--version, setup:db:status, deploy:mode:show
Modes	deploy:mode:set developer production
Modules	module:enable disable Vendor_Module, then setup:upgrade
Build	setup:upgrade, setup:di:compile, setup:static-content:deploy
Cache	cache:status, cache:clean (by tag), cache:flush (empties storage), cache:enable disable [type]
Indexers	indexer:status, indexer:reindex [id], indexer:set-mode schedule realtime
Cron	cron:install [--force], cron:remove, cron:run --group=<id>
Queues	queue:consumers:start <name> --max-messages=1
Config	config:set, config:show, setup:config:set
Other	maintenance:enable disable, encryption:key:change

Custom command: extend Symfony Command, add it to the commands argument of Magento\Framework\Console\CommandListInterface in di.xml.

MODULE SKELETON

```
app/code/Vendor/Module/
registration.php composer.json
etc/module.xml di.xml config.xml
events.xml acl.xml webapi.xml
crontab.xml db_schema.xml
db_schema_whitelist.json
schema.graphqls csp_whitelist.xml
queue*.xml frontend/routes.xml
adminhtml/{routes,menu,system}.xml
Setup/Patch/{Data,Schema}/
Controller/ Block/ Model/ Api/ Plugin/
Observer/ ViewModel/
view/{frontend,adminhtml}/
{layout,templates,web}
<module name="Vendor_Module"><sequence>
<module name="Magento_Catalog"/>
</sequence></module>
```

Without registration.php a Composer module is never registered. setup_version is legacy; use patches.

di.xml, PLUGINS, EVENTS

```
<preference for="Vendor\Api\FooInterface"
  type="Vendor\Model\Foo"/>
<type name="Magento\Quote\Model\Quote">
  <plugin name="vendor_check"
    type="Vendor\Plugin\Check" sortOrder="10"/>
</type>
<type name="Vendor\Model\Counter"
  shared="false"/>
<virtualType name="VendorLog"
  type="Monolog\Logger"/>
<event name="checkout_submit_all_after">
  <observer name="vendor_placed"
    instance="Vendor\Observer\Placed"/>
</event>
```

Plugins wrap public, non-final, non-static methods of ObjectManager-built objects: beforeX (arguments), afterX (result), aroundX (to stop the chain; without \$proceed it hides later plugins). Lower sortOrder runs first. Observers implement ObserverInterface::execute(); a repeated observer name merges. shared="false" acts when injected.

SCHEMA AND PATCHES

etc/db_schema.xml is merged across modules and applied by setup:upgrade. **Adding and changing need no whitelist; removing does.** Commands: setup:db-declaration:generate-whitelist --module=Vendor_Module, setup:db-declaration:generate-patch.

- Generate the whitelist while the element is still in the XML; commit it each release; never with a DB prefix.
- Rename: onCreate="migrateDataFrom(old)".
- Disabling a module drops its whitelisted tables on the next setup:upgrade.

Patches implement DataPatchInterface or SchemaPatchInterface (Magento\Framework\Setup\Patch): apply(), static getDependencies(), getAliases(); they run once and are recorded in patch_list.

FRONTEND: LUMA THEME, LAYOUT, TEMPLATES

```
app/design/frontend/Vendor/name/
registration.php theme.xml
etc/view.xml requirejs-config.js
web/css/source/_extend.less _theme.less
Magento_Theme/layout/default.xml
Magento_Theme/templates/html/
copyright.phtml
<theme><title>My Theme</title>
<parent>Magento/luma</parent></theme>
```

- Templates and static files use **fallback** (theme, parents, module). Layout files merge by handle; layout/override/base/ replaces a module file.
- Handle = file name (catalog_product_view.xml); referenceContainer adds to a container. Entry points styles-m.less, styles-l.less.
- Production mode needs setup:static-content:deploy. Escape output in .phtml.

Alternatives: Hyvä (Tailwind CSS + Alpine.js, OSL-3.0/AFL-3.0), PWA Studio 14.5.1 (React, GraphQL), Commerce Storefront on Edge Delivery (Cloud Service).

REST, GRAPHQL, TOKENS

REST	/rest/V1/... /rest/<store-view>/V1/... /rest/all/V1/...
Async, bulk	/rest/<store>/async/V1/... /rest/<store>/async/bulk/V1/... :HTTP 202 + bulk_uuid: GET /V1/bulk/{uuid}/status
GraphQL	POST /graphql, optional Store header; schema.graphqls + resolver

webapi.xml resource: anonymous, self or an ACL id. Paging and filters: searchCriteria[filter_groups][0][filters][0][field][value][condition_type], [sortOrders], [pageSize], [currentPage].

Customer	POST /V1/integration/customer/token (username, password) or GraphQL generateCustomerToken: revoke: /V1/integration/customer/revoke-customer-token
Admin	POST /V1/integration/admin/token: with 2FA: /V1/tfa/provider/<provider>/authenticate
Integration	OAuth 1.0a HMAC-SHA256 signed requests
Cloud Service	Adobe IMS OAuth 2

Header Authorization: Bearer <token>. JWT HS256, 60 min (webapi/jwtauth/*_expiration). GraphQL limits: 10 aliases, 1,048,576 query characters, complexity 300, depth 20.

OUT-OF-PROCESS OPTIONS

App Builder	Node.js actions (Adobe I/O Runtime), aio CLI; any edition
I/O Events	Commerce to app via cron; Adobe Commerce 2.4.4+, not Open Source
Webhooks	Synchronous HTTPS; reply continues, stops or changes data
Admin UI SDK	Menus, pages, columns; 2.4.5+, not Open Source
App Management	app.commerce.config; hosted Commerce only
API Mesh	Merges GraphQL, REST, JSON into one endpoint

CLI: events:subscribe <code> --fields=<name>, events:list:all, events:info <code>. Event code: observer.<event> or plugin.<class.path>.<method>.

SECURITY CHECKLIST

- Patchfirst.** APSB26-146 (2026-09-07): CVE-2026-75650, score 10.0, unauthenticated code execution, hotfix VULN-39341 on every supported line, then rotate keys.
- Non-default Admin URI (--backend-frontname, random by default): less noise, not a control.
- Keep Magento_TwoFactorAuth on (Google Authenticator, Duo, Authy, U2F); retry limit 10, lockout 300 s since 2.4.8.
- CSP: payment pages restrict mode since 2.4.7, others report-only; whitelist hosts per policy in etc/csp_whitelist.xml.
- Code: escape output, form keys, ACL on every admin route, encrypted config for secrets.
- Scan: Security Scan Tool, composer audit, vendor/bin/phpcs --standard=Magento2.
- Incident: keep logs, patch, rebuild clean, encryption:key:change and encryption:data:re-encrypt core_config_data sales_order_payment; rotate admin, integration, OAuth, gateway and DB secrets.

CLOUD DEPLOYMENT: MANY PODS ON AMAZON EKS (CHECKED 2026-10-29)

Database. RDS for MySQL 8.4 or MariaDB 12.3, or Aurora MySQL 3 (listed by Adobe for 2.4.9); env.php reads the environment with TLS; mg_app and a migration user; split database is deprecated since 2.4.2.

State placement. Five services: RDS, OpenSearch 3.x, two Valkey groups (cache and sessions), Amazon MQ for RabbitMQ 4.3, S3 for media (remote storage driver, remote-storage:sync); Varnish StatefulSet for the full page cache; config.php committed, secrets in the environment; code, DI and static content built into the image.

Cron. One CronJob running cron:run --group=<id> --bootstrap=standaloneProcessStarted=1 per group; consumers as Deployments running queue:consumers:start scaled by KEDA, cron_consumers_runner off; indexers on Update by Schedule.

Release steps. Gate with setup:db:status; pre-upgrade Job setup:upgrade --keep-generated (or app:config:import); pause consumers and cron; rolling update behind Varnish; static content and DI are built into the image, so nothing is compiled at run time.

Key commands. bin/magento setup:db:status, indexer:status, queue:consumers:list, cache:status, config:show web/secure/base_url, helm upgrade pocketcoffee ./pocketcoffee-magento.