

Environment

`help f / doc f / lookfor kw`; which `--all f` shows every definition (shadowing); `whos, who, clear x, clc, close all`; `format long/short` (display only)

`save f.mat x y, load f.mat, matfile` (partial access); `addpath, path, pwd, cd; startup.m` runs at launch; batch: `matlab -batch "runtests"`

R2025a web-based desktop; R2026b: no Java installed, live scripts plain-text `.m` by default.

Syntax

```
x = 3;           % ; hides output, ans = last
%{ block comment %} ... continue line
%% section (Ctrl+Enter runs it)
hold on         % command syntax: words
hold("on")      % function syntax: same call
a = 1; b = 2, c = 3; % , shows, ; hides
```

Names: letter then letters/digits/_; case-sensitive; `iskeyword` lists keywords; avoid shadowing (`sum, max`). Values are copied lazily (copy-on-write).

Arrays

```
A = [1 2; 3 4];    v = 1:5; w = (0:4)/4;
linspace(0,1,5) zeros(2,3) ones(2)
eye(3)
rand(3) randn(3) randi(9,2) repmat(A,2,2)
[A B] horzcat [A; B] vertcat cat(3,A,A)
reshape(A,1,[]) permute(X,[2 1 3]) A.'
A'
size numel ndims length isempty
isvector
```

Column-major: `A(:)` reads down column 1, then column 2. 1-based. `[]` is 0-by-0; `zeros(0,3)` is not `[]`.

Indexing

```
A(i,j) A(k) A(end,:) A(:,2) A(:) A(2:end-1)
A(A>2)=0           % logical mask
A(2,:)=[]           % delete row
[r,c]=find(A>2)     i=sub2ind(size(A),r,c)
A(5,5)=1            % grows, pads with 0
```

	()	{}	.
array	elements	–	–
cell	sub-cell	contents	–
struct	element	–	field
table	sub-table	block as array	variable

`c{}` and `s.f` on struct arrays make comma-separated lists: `[c{:}]`, `f(c{:})`.

Operators

```
+ - * / \ ^ matrix .* ./ .^
element-wise
' conj-transpose .' transpose
== ~= < <= > >= & | ~ element-wise
&& || scalar short-circuit xor(a,b)
```

Precedence, high to low: `()`; transpose, power; unary `+-~`; `* / \ .* ./`; binary `+-;`; relational; `&`; `|`; `&&`; `||`.

Implicit expansion (R2016b): sizes are compatible if each dimension is equal or 1.

```
M = [1 2 3] + [10; 20] % 2-by-3
bsxfun not needed; [1 2 3]+[1 2] is an error
```

Types

Type	Notes
double single	IEEE 754; default double; <code>eps</code> , <code>Inf</code> , <code>NaN</code> ; <code>0.1+0.2~=0.3</code>
int8. uint64	<code>saturate(uint8(300)) = 255</code> , round to nearest; <code>intmax</code>
logical	true false; masks
char / string	'ab' vs "ab"
cell struct	{1,"a"}; s.f.s. ("f")
table timetable	T.Var, T(rows,:); time-stamped rows
datetime	<code>datetime("now")</code> , <code>days(2)</code>
duration	
categorical	<code>categorical(["a" "b"])</code>
dictionary (R2022b)	<code>d = dictionary("k",1); d("k")</code>
missing NaN	<code>ismissing</code> , <code>rmissing</code>
NaN	<code>fillmissing</code>
@handle	<code>f = @sin</code>

```
class(x), isa(x,"numeric"),
cast(x,"int16"), double(x).
```

Text

```
s = "heat" + "flow" % string: + joins
c = ['ab' 'cd']      % chars: [] joins
compose("T=%d",3) sprintf("%6.2f",pi)
split(s,"-") join(["a" "b"],",")
contains(s,"he") replace(s,"he","HE")
strlength upper strip extractBefore
regexp(s,'(w+)flow','tokens')
p = letterBoundary + digitsPattern;
extract(s,p)
str2double("3.5") string(7) num2str(7)
```

"..." arrays can hold any text and missing (`<missing>`); `'...'` is a numeric row of chars.

Control flow

```
if a>0, ... elseif a==0, ... else, ... end
switch s, case {"a","b"}, ... otherwise,
... end
for k = A % iterates over COLUMNS
while cond, ... break / continue, end
return % leave function
try, f(), catch ME, disp(ME.message), end
```

`if` on an array is true only if all elements are nonzero; use `any/all`.

Functions

```
function [y,n] = f(x,varargin) % f.m
arguments
x(1,:) double {mustBePositive}
opts.Tol(1,1) double = 1e-6
opts.Mode(1,1) string
{mustBeMember(opts.Mode,["a","b"])} = "a"
end
n = nargin; y = x.^2;
end
function h = local(x), end % local fn
(same file)
y = f(1:3, Tol=1e-3) % Name=Value
R2021a
g = @(x) x.^2 + 1; g(2) fn = @f
feval(fn,2)
[~,i] = max(v) nargin nargs varargout
global G persistent P % scope: avoid
global
```

Nested functions share the parent's variables; `private/` folder fns visible to parent only. Resolution order: variable, nested/local, private, class/namespace, path. `mustBeBetween` arrived in R2025a.

Errors & debugging

```
error("pkg:id","bad %d",x)
warning("pkg:w","...")
assert(x>0,"pkg:neg","x=%d",x)
try, f(), catch ME, rethrow(ME), end
ME = MEException("a:b","msg"); throw(ME)
c = onCleanup(@() fclose(fid));
dbstop if error dbstop dbcont dbquit
codeIssues("src") % Code Analyzer
```

classdef

```
classdef Plate < handle % value if no <
handle
properties (SetAccess=private)
T (:,:) double
end
properties (Dependent), Mean, end
methods
function obj = Plate(T), obj.T = T; end
function m = get.Mean(obj), m =
mean(obj.T,"all"); end
end
events StepCompleted, end
enumeration, Dirichlet, Neumann, end
end
addlistener(p,"StepCompleted",@(s,e)
disp("ok")); notify(p,"StepCompleted")
```

Folders: `+heatfLow/` namespace (R2024a name), `@Plate/` class folder. `?Plate` metaclass. Handle copies alias; value copies are independent.

Graphics

```
plot(x,y,"r-o","LineWidth",1.5); hold on
tiledlayout(2,1); nexttile; scatter(x,y)
title xlabel ylabel legend histogram(v)
[X,Y]=meshgrid(x,y); surf(X,Y,Z);
contour(X,Y,Z)
ax = gca; ax.XLim = [0 1]; % dot notation
exportgraphics(gcf,"f.png",Resolution=300)
```

Data I/O

```
T = readtable("sensors.csv");
writetable(T,"o.csv")
M = readmatrix("m.csv")
datastore("*.csv")
fid=fopen("f.txt","w");
fprintf(fid,"%d\n",5); fclose(fid);
s = jsondecode(txt); jsonencode(s)
cfg = readstruct("plate.json");
webread(url)
```

Maths

```
x = A\b (not inv(A)*b) det rank norm
cond
[V,D]=eig(A) [U,S,W]=svd(A) lu qr chol
S = sparse(1,j,v,m,n) spy nnz
p = polyfit(x,y,2); polyval(p,x);
interp1(x,y,xi)
integral(@f,0,1) [t,y]=ode45(@f,[0 1],y0)
fzero fminsearch fft/ifft rng(1)
mean(x,"omitmissing")
```

Performance

Vectorise; `preallocate(zeros(1,n))`; avoid growing in loops. `tic; toc, timeit(@f)`, `profile on`; `profile viewer`. `backgroundPool`, `parfeval`, `timer`, tall arrays.

Testing & build

```
% function test file
function tests = fooTest, tests =
functiontests(localfunctions); end
function t1(tc),
verifyEqual(tc,f(2),4,AbsTol=1e-9); end
% class test: classdef FooTest <
matlab.unittest.TestCase
% methods (Test), function t(tc), ...
end, end
runtests("tests")
% buildfile.m
function plan = buildfile
plan = buildplan(localfunctions);
plan("test") =
matlab.buildtool.tasks.TestTask("tests");
end % run: buildtool test
```

Interop

```
py.math.sqrt(2), pyenv(Version="3.13"),
pyrun("x=1"); R2026b supports Python 3.10 to
3.14 (3.14 new, 3.9 dropped). Python side: eng =
matlab.engine.start_matlab(), pip install
matlabengine. C/C++: mex f.c,
clibgen.generateLibraryDefinition.
javaObject (add OpenJDK in R2026b),
NET.addAssembly, system("ls").
```

Tools & sharing

Live scripts: plain-text `.m` (R2025a, default R2026b) or binary `.mlx`. App Designer (GUIDE removed R2025a). Projects with `matlab.toml` (R2026b). `mpminstall/mpmcreate` (MATLAB Package Manager, R2024b). `pcode f.m` hides source (not secure). MATLAB Vault for secrets. GNU Octave runs much code but not all; Octave 11.3.0.