

Ruby Cheat Sheet

Ruby 4.0 (4.0.7) · checked 2026-10-18 · Irurueta Docs · AI-assisted; verify against docs.ruby-lang.org/en/4.0

TOOLS & FLAGS

```
ruby f.rb run -irb REPL · ri Array#map
docs · gem · bundle · rake -T · rdbg f.rb ·
rbs validate · rubocop -a

ruby -e 'puts 1+1' -w warnings -c
syntax check
ruby -n/-p -l -a -i one-liners -r
lib -I dir
ruby --yjit f.rb --zjit
(experimental)
ruby -W:no-experimental RUBYOPT=-w
```

GEMFILE & GEMSPEC

```
source "https://rubygems.org"
gemspec
gem "rake", "~> 13.0"
group :development, :test do
  gem "minitest"; gem "rubocop"
end
# shelf.gemspec
Gem::Specification.new do |s|
  s.name = "shelf"; s.version =
  "0.1.0"
  s.summary = "Library catalogue"
  s.license = "MIT"
  s.required_ruby_version = ">= 4.0"
  s.binder = "exe"; s.executables =
  ["shelf"]
  s.add_dependency "json", "~> 2.9"
  s.metadata["rubygems_mfa_required"] =
  "true"
end

bundle init|install|add
x|update|exec|outdated · bundle gem
shelf · gem build|push · Gemfile.lock
committed for apps. Default gems ship with
Ruby and are locked in; bundled gems
(benchmark, logger, ostruck...) need a Gemfile
line when bundling.
```

FILE BASICS

```
# frozen_string_literal: true #
first lines
require "json" # gem /
stdlib
require_relative "shelf/book"
autoload :Loan, "shelf/loan"
__FILE__ == $PROGRAM_NAME # run as
script
snake_case methods/vars · CamelCase classes
· SCREAMING consts · ? predicate · ! dangerous
· _ unused · 2-space indent.
```

LITERALS

```
1_000 0xff 0b1 0o7 1.5e3 3r 2i
"a#{1+1}" 'raw' :sym :%a b" %w[a
b] %i[a b]
<<<TXT # squiggly heredoc
indented
TXT
[1, 2] {a: 1, "b" => 2} {x:, y:} #
y: shorthand
(1..3) (1..3) (1..) (..5) /re/i
%r{a/b}
-> (a, b = 2) { a + b } # call: l.
(1) l[1]

Falsy: only nil and false (0, "", [] are truthy).
p({a: 1, "b" => 2}) prints {a: 1, "b" =>
2} (3.4+).
```

VARIABLES & ASSIGNMENT

x	local (block/method scope)
@x	instance
@@x	class var (avoid; use class-level @@x)
\$x	global
X	constant (reassign warns)

```
a ||= 1 a &&= 2 a += 1
a, b = b, a
first, *rest = [1, 2, 3]
a, (b, *c), d = 1, [2, 3, 4], 5
h => {name:} # rightward
destructure
x = if c then 1 else 2 end #
expression
```

OPERATORS & PRECEDENCE

High → low: ! ~ +@ > ** > -@ > * / % > + -
> < >> > & > | ^ > < < > > > >
<<> == === =~ != > && > || > > ?:
> modifier-rescue > = op > not > and or >
modifier-if/unless/while.
&&/|| bind tighter than and/or (control flow
only). obj&.m nil-safe · === case equality · =~
regexp <<> returns 1/0/1/nil · 7 / 2 #=> 3,
-7 / 2 #=> -4, 7.fdiv(2) #=> 3.5.

CONTROL

```
if a then b elsif c then d else e end
x = 1 if ok puts "no" unless ok
case v
when 1..5, Integer then :int
when /re/ then :re
else :other end
while c; end until c; end loop {
break }
3.times { } 1.upto(3) { } for i in
1..3 do end
break next redo return
catch(:done) { throw :done, 42 } #=>
42
```

METHODS & ARGUMENTS

```
def m(a, b = 1, *rest, c, k:, k2: 2,
**opts, &blk) = ... # this
order
def area = w * h #
endless
def fwd(...) = target(...)
def anon(*, **, &) = target(*, **, &)
m(1, *arr, k: 1, **h, &:sym)
def a? = true def x(v); @x = v; end

Keyword args are separate from positional
hashes (3.0). Defaults evaluate per call. Implicit
return = last expression. private / protected /
public; private def f;
private_class_method; implicit-receiver call or
literal self.f.
```

BLOCKS, PROCS, LAMBDAS

```
[1, 2].map { it * 2 } # 3.4 it
[1, 2].map { _1 + 1 } # numbered
param
def each = block_given? ? yield(1) :
to_enum
%w[a b].map(&:upcase) m =
1.method(:+)
f = :upcase.to_proc >>
reverse.to_proc
f.call("ab") #=> "BA"
```

	proc	lambda
args	lenient, arity 2	strict
return	returns from method	returns from lambda

EXCEPTIONS

```
begin
risky
rescue KeyError, TypeError => e
warn e.message
else ok
ensure cleanup
end # retry re-runs begin
class AppError < StandardError; end
raise AppError, "msg" raise X.new,
cause: e

Bare rescue = StandardError. Never rescue
Exception. Exception → NoMemoryError,
ScriptError (LoadError,
NotImplementedError, SyntaxError),
SecurityError, SignalException
(Interrupt), SystemExit, SystemStackError,
StandardError (ArgumentError, IOError,
IndexError → KeyError/StopIteration,
NameError → NoMethodError, RangeError,
RuntimeError → FrozenError, TypeError,
ZeroDivisionError,
NoMatchingPatternError).
```

OBJECT MODEL

```
class Book < Item
include Comparable # after class
in ancestors
prepend Audit # before class
extend Finders # class-level
methods
attr_reader :title; attr_accessor :n
def initialize(title) = @title =
title
class << self; def build = new("t");
end
def <=>(o) = title <=> o.title
def to_s = "Book #{title}"
end
Book.ancestors #=> [Audit, Book,
Comparable, Item, ...]

Lookup: singleton → prepended → class →
included (last first) → superclass. super (same
args) · super() (none) · super(a). Refinements:
refine String do;end; using M (file-scoped).
module_function.
```

EQUALITY & COPYING

```
equal? identity · == value · eql? + hash Hash
key(1.eql?(1.0) #=> false) · === case.
Define ==, eql?, hash together; include
Comparable adds < > between? clamp.
a.dup # shallow, unfrozen
a.clone # shallow, keeps frozen &
singleton
a.clone(freeze: false) a.freeze
a.frozen?
FrozenError: can't modify frozen
Array: [1]
```

CORE TYPES

```
7.divmod(2) #=> [3, 1] 10.pow(3, 7)
#=> 6
Integer.sqrt(17) #=> 4 1r/3 #=> (1/3)
2**-1 #=> (1/2)
"abc"[1..] #=> "bc" "a-b".tr("-", "_")
"%05.1f[%-4s]%" % [3.14159, "ab", 5]
"x".sub(x/) { it.upcase } s.freeze
+"" / -""
:ab.to_proc "ab".to_sym :ab.name
[1,2,3].first(2) [1,[2]].flatten
a[1..] a.dig(0,1)
h.fetch(k) #=> KeyError "key not
found: :k"
h.dig(:a, 0, :b) h.transform_values {
it + 1 }
Set[1, 2] | Set[3] #=> Set[1, 2, 3]
# core in 4.0
(1..10).step(3).to_a (1..).lazy.map {
}, first(3)
Time.utc(2026,10,18).iso8601
Time.now.strftime("%F")
Process.clock_gettime(
Process::CLOCK_MONOTONIC)
```

STRUCT vs DATA

```
Book = Data.define(:isbn, :title) do
def label = "#{title} #{isbn}"
end
b = Book.new(isbn: "1", title: "T")
b.with(title: "U") b.to_h #
immutable
#=> #<data Book isbn="1", title="T">
Loan = Struct.new(:a, :b,
keyword_init: true)
#=> #<struct Loan a=1, b=2> # mutable

Data: immutable value objects, keyword or
positional, with, pattern-matchable. Struct:
mutable, enumerable.
```

REGEXP

```
m = "2026-10".match(/(?<y>\d+)-(?
<m>\d+)/)
ml[:y] #=> "2026" $~ $1
/(?<y>\d+)-/ =~ s # makes local yr
s.scan(/d+/) s.gsub(/a/, "b") s =~
/re/
\A \z anchors (not ^ $)
Regexp.timeout = 1.0
```

ENUMERABLE

```
map select reject filter_map flat_map
find
reduce(+) sum min_by max_by
sort_by { -it }
group_by(&:odd?) partition tally
zip
each_slice(2) each_cons(2)
each_with_index
each_with_object({}) take_while
chunk_while
%w[a b a].tally #=> {"a" => 2, "b" =>
1}
(1..6).each_slice(2).to_a #=> [[1, 2],
[3, 4], [5, 6]]

Include Enumerable + define each. No block →
Enumerator: next, peek, with_index, lazy,
Enumerator.new { |y| y << 1 }.
```

PATTERN MATCHING

```
case cfg
in {name: String => n, roles: [:a,
*rest]} then ..
in [Integer => x, *] | [] then ..
in [* , String => s, *post] then .. #
find
in Integer | Float => num if num > 0
then ..
in ~v | ^v + 1 then ..
# pin
in nil then ..
end
42 in Integer #=> true (boolean)
{:a: 1} => {:a:} # binds a, raises
NoMatchingPatternError

Custom: define deconstruct (array) /
deconstruct_keys(keys) (hash).
```

METAPROGRAMMING

```
obj.send(:x) obj.public_send(:x) #
respects private
Foo.define_method(:dbl) { n * 2 }
def method_missing(name, *args)
name.start_with?("get_") ?
name.to_s.delete_prefix("get_") :
super
end
def respond_to_missing?(n, priv =
false) = n.start_with?("get_") ||
super
instance_eval { @a } class_eval { }
def self.inherited(k) = (super; ...)
# hooks:
included extended prepended
method_added const_added
obj.instance_variables
Foo.instance_methods(false)

Never send/eval/constantize untrusted
input; use allow-lists.
```

CONCURRENCY

```
t = Thread.new { 5 }; t.value #=> 5
t.join
m = Mutex.new; m.synchronize { }
q = Queue.new; q << 1; q.pop
SizedQueue.new(10)
f = Fiber.new { Fiber.yield 1; 2 }
f.resume #=> 1 f.resume #=> 2
Fiber.set_scheduler(s) # non-blocking
I/O
# Ractor (experimental, 4.0 API)
p = Ractor::Port.new
Ractor.new(p) { |pt| pt << 42 };
p.receive #=> 42
Ractor.new { 1 + 1 }.value #=> 2

GV: one thread runs Ruby code at a time;
threads overlap on I/O. CPU parallelism →
processes or Ractors. Set
report_on_exception. Ractor.yield/take are
gone in 4.0.
```

STDLIB ONE-LINERS

```
File.read(p) File.write(p, s)
File.open(p) { |f| }
Dir.glob(*.rb)
Pathname("a/b.rb").extname
Open3.capture2(["echo", "hi"]) #=>
["hi\n", status]
system("ls", "-l") # array form, no
shell
Net::HTTP.get(URI("https://x.test/a"))
JSON.parse(s, symbolize_names: true)
h.to_json
YAML.safe_load(s, symbolize_names:
true)
OptionParser.new { |o| o.on("-v") { }
}.parse!
Logger.new($stdout).info("x")
CSV.read(p, headers: true)
Benchmark.realtime { work }
GC.stat(:count)

Never Marshal.load/YAML.unsafe_load
untrusted data.
```

TESTING & QUALITY

```
require "minitest/autorun"
class BookTest < Minitest::Test
def test_title = assert_equal "T",
Book.new("T").title
end
describe Book do # Minitest::Spec
it("has a title") {
(Book.new("T").title).must_equal "T"
}
end
RSpec.describe Book do
let(:b) { Book.new("T") }
it { expect(b.title).to eq("T") }
let(:repo) { instance_double(Repo,
find: nil) }
end
# sig/shelf.rbs
class Shelf:Book
attr_reader title: String
def initialize: (String title) ->
void
end
end
rubocop -a rubocop -A rubocop --
auto-gen-config
```

PERFORMANCE & VM

```
--yjit or RUBY_YJIT_ENABLE=1 or
RubyVM::YJIT.enable --zjit experimental ·
Prism parser → YARV bytecode · MJIT/RJIT gone
· GC.stat, GC.start · Benchmark.realtime {
}, benchmark-ips (community) ·
Process.clock_gettime with
CLOCK_MONOTONIC for timing. Generational +
incremental GC; tune with RUBY_GC_* env vars.
C extensions: extconf.rb + mkmf; Fiddle
(bundled gem 4.0); ffi gem; ruby.wasm for
browsers/GAS.
```

CHANGED SINCE OLDER TUTORIALS (with version)

3.0 keyword args separated from positional hashes
3.0-3.2 \$SAFE / taint removed
3.2 Fixnum / Bignum, File.exists? removed
3.2 Struct hacks → Data.define
3.4 _1 → it

3.4 chilled string literals warn on mutation (-W:deprecated)
3.4 {:a=>1} → {:a: 1} inspect; new error format undefined
method 'x' for an instance of Foo
3.4-4.0 OpenStruct, benchmark, logger... become bundled gems
(Gemfile)

4.0 require "set" not needed: core Set; Pathname core
4.0 Kernel#open("|cmd") removed (use IO.popen/Open3)
4.0 Ractor.yield/take → Ractor::Port, #value
3.3/4.0 MJIT (3.3) and RJIT (4.0) removed: YJIT (and experimental
ZJIT)